



1. Flange size as per BSEN1092-2:1997 PN16
2. Ductile iron as per BSEN1563:1997 Grade 450/10
3. Coating:
Interior : minimum of 0.3mm of powder epoxy.
Exterior : minimum of 0.3mm of powder epoxy.
5. Brandname : Sino-flex

NO	PARTS	MATERIAL	REMARK
12	Bolts	Stainless Steel	SS304
11	Bolts	Stainless Steel	SS304
10	O-ring	Rubber	NBR
9	O-ring	Rubber	NBR
8	Fixing Nut	Plastic	PE
7	Air Vent base	Rubber	SBR
6	Lift Valve	Plastic	PE
5	Floot	Stainless Steel	SS304
4	Floot Holder	Plastic	ABS
3	Lid	Ductile Iron	BSEN1563:1997 Grade 450/10
2	Upper Part	Ductile Iron	BSEN1563:1997 Grade 450/10
1	Body	Ductile Iron	BSEN1563:1997 Grade 450/10

△	CHECKED BY		APPROVED BY	
△	DRAWN BY	Y.K.H	DESIGNED BY	Y.K.H
△	MATERIAL	-	SCALE	ANGLE PRO.
△	UNIT	mm	NTS	
REMARK				
YUNG YU SPECIAL JOINT CO., LTD.			DRAWING NO. R27B0323-1	
AIR RELEASE VALVE				